

§ 412.10

reductions that would be achieved by the 100-foot setback.

Subpart A—Horses and Sheep

§ 412.10 Applicability.

This subpart applies to discharges resulting from the production areas at horse and sheep CAFOs. This subpart does not apply to such CAFOs with less than the following capacities: 10,000 sheep or 500 horses.

§ 412.11 [Reserved]

§ 412.12 Effluent limitations attainable by the application of the best practicable control technology currently available (BPT).

(a) Except as provided in 40 CFR 125.30 through 125.32, and subject to the provisions of paragraph (b) of this section, any existing point source subject to this subpart must achieve the following effluent limitations representing the application of BPT: There shall be no discharge of process waste water pollutants to navigable waters.

(b) Process waste pollutants in the overflow may be discharged to navigable waters whenever rainfall events, either chronic or catastrophic, cause an overflow of process waste water from a facility designed, constructed and operated to contain all process generated waste waters plus the runoff from a 10-year, 24-hour rainfall event for the location of the point source.

§ 412.13 Effluent limitations attainable by the application of the best available technology economically achievable (BAT).

(a) Except as provided in 40 CFR 125.30 through 125.32 and when the provisions of paragraph (b) of this section apply, any existing point source subject to this subpart must achieve the following effluent limitations representing the application of BAT: There shall be no discharge of process waste water pollutants into U.S. waters.

(b) Whenever rainfall events cause an overflow of process wastewater from a facility designed, constructed, operated, and maintained to contain all process-generated wastewaters plus the runoff from a 25-year, 24-hour rainfall

40 CFR Ch. I (7–1–08 Edition)

event at the location of the point source, any process wastewater pollutants in the overflow may be discharged into U.S. waters.

§ 412.14 [Reserved]

§ 412.15 New source performance standards (NSPS).

(a) Except as provided in paragraph (b) of this section, any new source subject to this subpart must achieve the following performance standards: There must be no discharge of process wastewater pollutants into U.S. waters.

(b) Whenever rainfall events cause an overflow of process wastewater from a facility designed, constructed, operated, and maintained to contain all process-generated wastewaters plus the runoff from a 25-year, 24-hour rainfall event at the location of the point source, any process wastewater pollutants in the overflow may be discharged into U.S. waters.

Subpart B—Ducks

§ 412.20 Applicability.

This subpart applies to discharges resulting from the production areas at dry lot and wet lot duck CAFOs. This subpart does not apply to such CAFOs with less than the following capacities: 5,000 ducks.

§ 412.21 Special definitions.

For the purposes of this subpart:

(a) *Dry lot* means a facility for growing ducks in confinement with a dry litter floor cover and no access to swimming areas.

(b) *Wet lot* means a confinement facility for raising ducks which is open to the environment, has a small number of sheltered areas, and with open water runs and swimming areas to which ducks have free access.

§ 412.22 Effluent limitations attainable by the application of the best practicable control technology currently available (BPT).

(a) Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart shall

Environmental Protection Agency

§412.31

achieve the following effluent limitations representing the degree of efflu-

ent reduction attainable by the application of the (BPT):

Regulated parameter	Maximum daily ¹	Maximum monthly average ¹	Maximum daily ²	Maximum monthly average ²
BOD ₅	3.66	2.0	1.66	0.91
Fecal coliform	(³)	(³)	(³)	(³)

¹ Pounds per 1000 ducks.

² Kilograms per 1000 ducks.

³ Not to exceed MPN of 400 per 100 ml at any time.

(b) [Reserved]

§§ 412.23–412.24 [Reserved]

§412.25 New source performance standards (NSPS).

(a) Except as provided in paragraph (b) of this section, any new source subject to this subpart must achieve the following performance standards: There must be no discharge of process waste water pollutants into U.S. waters.

(b) Whenever rainfall events cause an overflow of process wastewater from a facility designed, constructed, operated, and maintained to contain all process-generated wastewaters plus the runoff from a 25-year, 24-hour rainfall event at the location of the point source, any process wastewater pollutants in the overflow may be discharged into U.S. waters.

§412.26 Pretreatment standards for new sources (PSNS).

(a) Except as provided in 40 CFR 403.7 and in paragraph (b) of this section, any new source subject to this subpart must achieve the following performance standards: There must be no introduction of process waste water pollutants to a POTW.

(b) Whenever rainfall events cause an overflow of process wastewater from a facility designed, constructed, operated, and maintained to contain all process-generated wastewaters plus the runoff from a 25-year, 24-hour rainfall event at the location of the point source, any process wastewater pollutants in the overflow may be introduced to a POTW.

Subpart C—Dairy Cows and Cattle Other Than Veal Calves

§412.30 Applicability.

This subpart applies to operations defined as concentrated animal feeding operations (CAFOs) under 40 CFR 122.23 and includes the following animals: mature dairy cows, either milking or dry; cattle other than mature dairy cows or veal calves. Cattle other than mature dairy cows includes but is not limited to heifers, steers, and bulls. This subpart does not apply to such CAFOs with less than the following capacities: 700 mature dairy cows whether milked or dry; 1,000 cattle other than mature dairy cows or veal calves.

§412.31 Effluent limitations attainable by the application of the best practicable control technology currently available (BPT).

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must achieve the following effluent limitations representing the application of BPT:

(a) *For CAFO production areas.* Except as provided in paragraphs (a)(1) through (a)(2) of this section, there must be no discharge of manure, litter, or process wastewater pollutants into waters of the U.S. from the production area.

(1) Whenever precipitation causes an overflow of manure, litter, or process wastewater, pollutants in the overflow may be discharged into U.S. waters provided:

(i) The production area is designed, constructed, operated and maintained to contain all manure, litter, and process wastewater including the runoff and the direct precipitation from a 25-year, 24-hour rainfall event;